



SKF FNL 513 B

FNL cast flanged, non-split housing

FNL cast flanged, non-split housings are well-proven machine parts that provide simple and reliable housing in applications without horizontal frames. They enable the full service life potential of the incorporated bearings to be exploited with less need for maintenance. FNL housings are supplied with a cover either for shaft ends (suffix A) or for through shafts (suffix B). Smaller sizes (up to and including size 13) have a triangular flange, larger sizes have a square flange.

Technical specifications

Dimensions	
Diameter of bearing seat	120 mm
Width of bearing seat	33 mm
Centre height of bearing seat	78 mm
Distance bearing seat to support surface	22 mm
Shaft diameter	60 mm
Base width	60 mm
Foot width	15 mm
Width	86 mm
Outside diameter of housing cover	152 mm
Thread of relubrication holes	1/8-27 NPSF
Height	203 mm
Length	225 mm
Pitch diameter of attachment bolts	190 mm
Diameter of attachment bolt hole	14 mm
Position of dowel pin	90 mm
Position of dowel pin	24 mm
Position of dowel pin	66 mm
Position of dowel pin	66 mm
Position of dowel pin	24 mm
Position of dowel pin	90 mm
Diameter of dowel pins	8 mm
Pitch diameter of bolt holes of round and triangle flange type housing	190 mm
Attachment bolt diameter	12 mm
Breaking loads	
Breaking load	130 kN
Breaking load	110 kN
Breaking load	190 kN
Materials	
Housing	Cast iron
Corrosion protection	Paint - in accordance with ISO 12944-2, corrosivity category C2
Mounting information	
Size of cover bolt	M6x20
Recommended tightening torque for cover bolts	10 N·m
Recommended diameter of attachment bolts	12 mm
Recommended tightening torque for attachment bolts	80 N·m
Initial grease fill, 20%	44 g
Initial grease fill, 40%	72 g
Included products	
Grease fitting	AH 1/8-27 PTF
Properties	

Housing type	Flanged
Housing configuration	One-piece
Mounting arrangement	Through shaft
Number of bolt holes for fasteners	3
Material, housing	Cast iron
Bearing housing seal type	Lip seal
Housing lubrication feature/possibility	Grease

Logistics	
Product net weight	6.4 kg
eClass code	23-05-17-02
UNSPSC code	31171519



