



SKF 65X95X10 HMSA10 RG

Radial shaft seal with rubber outside diameter and single sealing lip, for oil or grease.

Radial shaft seals are used between rotating and stationary machine components, or between components in relative motion. HMSA10 seals are designed with a rubber outside diameter. They have a conventional sealing lip made of elastomer. A garter spring in the seal and a non-contacting auxiliary lip optimize the sealing against the shaft also in polluted environment.

Technical specifications

General	
Type of outside diameter	Rubber metal reinforced
Lip material	Nitrile rubber (NBR)
Seal design	HMSA10
Compliance with standard	ISO 6194; DIN 3760
Dimensions	
Shaft diameter	65 mm
Housing bore diameter	95 mm
Seal width	10 mm
Application and operating conditions	
Operating temperature	-40 °C
Operating temperature	100 °C
Operating temperature, short periods	120 °C
Circumferential speed	8.9 m/s
Rotational speed	2640 r/min
Pressure differential	0.05 N/mm ²
Associated products	
SKF Speedi-Sleeve	99254
Performance	
Limiting speed	2640 r/min
Maximum operating temperature	100 °C
Minimum operating temperature	-40 °C
Permissible circumferential speed	8.9 m/s
Rotational speed	2640 r/min
Properties	
Design	HMSA10
Auxiliary lip	Yes
Sealing lip material	Nitrile rubber (NBR)
Type of outside diameter	Rubber metal reinforced
Unit system	Metric
Logistics	
Product net weight	0.0536 kg
eClass code	23-07-08-01
UNSPSC code	31181602

SKF drawings

