



SKF HK 1015

Drawn cup needle roller bearing with open ends

Drawn cup needle roller bearings are typically used in applications where the housing bore cannot be used as a raceway for a needle roller and cage assembly, but where a very compact and economical bearing arrangement is required. Owing to their large number of rollers, the bearings have a high load carrying capacity and stiffness.

Technical specifications

Dimensions	
Diameter under rollers	10 mm
Outside diameter	14 mm
Width	15 mm
Chamfer dimension drawn cup (outer ring)	0.4 mm
Bore diameter of needle roller complement	10 mm

Calculation data	
Basic dynamic load rating	6.6 kN
Basic static load rating	9 kN
Fatigue load limit	1.02 kN
Reference speed	18000 r/min
Limiting speed	20000 r/min

Associated products	
Inner ring IR series	IR 7x10x16
Radial shaft seal with a low cross-sectional height, single lip	G 10x14x3

Performance	
Basic dynamic load rating	6.6 kN
Basic static load rating	9 kN
Reference speed	18000 r/min
Limiting speed	20000 r/min

Properties	
Bearing part	Bearing without inner ring
Number of rows	1
Outer ring type	Drawn cup with open ends
Aligning feature	Without
Cage	Sheet steel
Number of flanges, outer ring	2
Tolerance class	Normal
Material, bearing	Bearing steel
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	0.02 kg CO ₂ e

Logistics	
Product net weight	0.0057 kg
eClass code	23-05-09-03
UNSPSC code	31171512

SKF drawings