



SKF PCMF 161817 E

Втулка/принадлежность подшипника SKF

Закрепительные и стяжные втулки обеспечивают монтаж подшипников с коническим отверстием на гладкий вал. Применяются для сферических роликоподшипников.

Характеристики

General	
Материал	PTFE composite
Operating temperature	-200 °C
Operating temperature	250 °C

Размеры	
Внутренний диаметр (d)	16 mm
Наружный диаметр (D)	18 mm
Ширина (B)	17 mm
Outside diameter flange	24 mm
Width flange	1 mm
Length chamfer bore - axial direction	0.1 mm
Length chamfer bore - axial direction	0.6 mm
Length chamfer outside diameter - axial direction	0.2 mm
Length chamfer outside diameter - axial direction	1 mm
Radius flange/bushing outside diameter	1 mm
Flange diameter	24 mm
Flange thickness	1 mm

Recommended fits	
Tolerance shaft	f7
Tolerance housing	H7

Расчётные данные	
Basic dynamic load rating, radial direction	18.6 kN
Basic static load rating, radial direction	58.5 kN
Basic dynamic load rating, axial direction	8.5 kN
Basic static load rating, axial direction	26.5 kN
Specific dynamic load factor	80 N/mm ²
Specific static load factor	250 N/mm ²
Factor depending on material and bearing type	480
Permissible sliding velocity	2 m/s
Coefficient of friction	0.03
Coefficient of friction	0.25

Характеристики	
Basic dynamic load rating, radial direction	18.6 kN
Basic static load rating, radial direction	58.5 kN
Basic dynamic load rating, axial direction	8.5 kN
Basic static load rating, axial direction	26.5 kN

Свойства	
Конструкция	Фланцевый
Материал	PTFE composite
Возможность пополнения смазки	Без

Логистика	
Масса нетто	0.0078 kg

Код eClass	23-05-01-90
Код UNSPSC	31171605

Чертежи SKF

