



SKF NKIB 5908

Combined needle roller / angular contact ball bearing for axial loads in both directions

These bearings consist of a radial needle roller bearing combined with an angular contact ball bearing. Together they can accommodate both heavy radial loads and light axial loads in both directions. In addition, they can operate at high speeds. Their low cross-sectional height makes the bearings particularly suitable for applications where other types of locating bearing arrangements occupy too much space.

Technical specifications

Dimensions	
Bore diameter	40 mm
Outside diameter	62 mm
Width	34 mm
Width of outer ring	30 mm
Diameter of inner ring raceway	48 mm
Chamfer dimension	0.6 mm
Width, outer ring	30 mm

Abutment dimensions	
Diameter of shaft abutment	44 mm
Diameter of housing abutment	58 mm
Radius of fillet	0.6 mm

Calculation data	
Basic dynamic load rating, radial	42.9 kN
Basic static load rating, radial	71 kN
Basic dynamic load rating, axial	7.17 kN
Basic static load rating, axial	10.9 kN
Fatigue load limit, radial	8.8 kN
Fatigue load limit, axial	0.467 kN
Reference speed	8000 r/min
Limiting speed	9500 r/min

Performance	
Reference speed	8000 r/min
Limiting speed	9500 r/min

Properties	
Rolling bearing type	Needle roller / angular contact ball bearing
Bearing part	Complete bearing
Thrust part	With cage
Radial part	With cage
Rolling element (thrust part)	Balls
Axial load capability	Double-direction
Radial internal clearance	CN
Tolerance class	Not applicable
Material, bearing	Bearing steel
Coating	Without
Lubricant (thrust part)	None
Indicative carbon footprint for new product	1.2 kg CO ₂ e

Logistics	
Product net weight	0.33 kg
eClass code	23-05-09-03
UNSPSC code	31171512

SKF drawings

