



SKF NU 206 ECP/C3

Single row cylindrical roller bearing, NU design

Single row cylindrical roller bearings are designed to accommodate high radial loads in combination with high speeds. Having two integral flanges on the outer ring and no flanges on the inner ring, NU design bearings can accommodate axial displacement in both directions. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.

Technical specifications

| Dimensions | |
|------------------|-------|
| Bore diameter | 30 mm |
| Outside diameter | 62 mm |
| Width | 16 mm |

| Performance | |
|---------------------------|--------------|
| Basic dynamic load rating | 44 kN |
| Basic static load rating | 36.5 kN |
| Reference speed | 13000 r/min |
| Limiting speed | 14000 r/min |
| SKF performance class | SKF Explorer |

| Properties | |
|---|---------------------------|
| Bearing part | Complete bearing |
| Axial displacement capability | In both directions |
| Number of rows | 1 |
| Locating feature, bearing outer ring | Without |
| Bore type | Cylindrical |
| Cage | Non-metallic |
| Number of flanges, outer ring | 2 |
| Number of flanges, inner ring | 0 |
| Loose flange | None |
| Radial internal clearance | C3 |
| Tolerance class | Normal |
| Coating | Without |
| Sealing | Without |
| Lubricant | None |
| Relubrication feature | Without |
| Indicative carbon footprint for new product | 0.73 kg CO ₂ e |

| Logistics | |
|--------------------|-------------|
| Product net weight | 0.202 kg |
| eClass code | 23-05-09-01 |
| UNSPSC code | 31171505 |