



SKF YEL 207-107-2F

Insert bearing with an eccentric locking collar and extended inner ring

Insert bearings are based on sealed deep groove ball bearings. This variant is intended for use in applications where the direction of rotation is constant. It has an inner ring extended on both sides, with an eccentric locking collar, enabling quick and easy mounting onto the shaft.

Technical specifications

Dimensions	
Bore diameter	36.513 mm
Outside diameter	72 mm
Overall bearing width	51.1 mm
Width of inner ring	37.6 mm
Width of outer ring	19 mm
Outside diameter of inner ring	46.1 mm
Outside diameter of locking collar	51.1 mm
Distance from side face to thread centre	6.75 mm
Chamfer dimension of inner ring	1 mm
Distance from locking device side face to raceway centre	32.3 mm
Shaft diameter	36.513 mm
Width, total	51.1 mm
Width, inner ring	37.6 mm
Width, outer ring	19 mm

Calculation data	
Basic dynamic load rating	25.5 kN
Basic static load rating	15.3 kN
Fatigue load limit	0.655 kN
Limiting speed	5300 r/min
	Limiting speed with shaft tolerance h6
Calculation factor	14

Mounting information	
Set screw	3/8-24 UNF
Hexagonal key size for set screw	4.763 mm
Recommended tightening torque for set screw	16.5 N·m

Associated products	
Rubber seating ring	RIS 207 A

Performance	
Basic dynamic load rating	25.5 kN
Basic static load rating	15.3 kN
Limiting speed	5300 r/min
Note	Limiting speed with shaft tolerance h6

Properties	
Retaining feature, inner ring	Eccentric collar
Bore type	Cylindrical
Rolling elements	Balls
Outer ring type	Spherical
Inner ring extension	On both sides
Cage	Non-metallic
Rubber seating ring	Without
Material, bearing	Bearing steel
Coating	Without

Sealing	Seal and flinger on both sides
Sealing type	Contact, standard
Lubricant	Grease
Relubrication feature	With

Logistics	
Product net weight	0.5 kg
eClass code	23-05-08-02
UNSPSC code	31171536

SKF drawings

