



SKF SNL 212

Корпусная деталь / стопорная шайба SKF

Корпуса и стопорные шайбы — вспомогательные элементы для монтажа подшипников. Обеспечивают фиксацию и защиту от осевого смещения.

Характеристики

Размеры	
Diameter of bearing seat	110 mm
Tolerance class of bearing seat diameter	G7
Width of bearing seat	48 mm
Centre height of bearing seat	70 mm
Внутренний диаметр (d)	87 mm
Overall width	105 mm
Foot width	70 mm
Thread of relubrication holes	1/8-27 NPSF
Overall height	134 mm
Foot height	30 mm
Overall length	255 mm
Distance between attachment bolts	210 mm
Length of attachment bolt hole	24 mm
Width of attachment bolt hole	18 mm
Inside width between seal grooves	79 mm
Width of seal groove	5 mm
Distance to seal groove back face	9 mm
Width at bore diameter	12 mm
Diameter of seal groove	95.5 mm
Distance between dowel pins	234 mm
Axial offset of dowel pins	27 mm
Diameter of dowel pins	8 mm
Высота центра (пиллоу-блок)	70 mm
Расстояние между болтами	210 mm
Attachment bolt diameter	16 mm

Расчётные данные	
Breaking load at 0° load angle (if the housing is not supported over its entire base)	210 kN
Breaking load at 55° load angle	300 kN
Breaking load at 90° load angle	180 kN
Breaking load at 120° load angle	130 kN
Breaking load at 150° load angle	120 kN
Breaking load at 180° load angle	150 kN
Breaking load, axial	100 kN
Load to reach yield point at 120° load angle	220 kN
Load to reach yield point at 150° load angle	125 kN
Load to reach yield point at 180° load angle	110 kN

Materials	
Housing material	Чугун
Corrosion protection	Paint - in accordance with ISO 12944-2, corrosivity category C2

Информация по монтажу	
Recommended diameter of attachment bolts	16 mm
Recommended tightening torque for attachment bolts	200 N·m

Size of cap bolts	M12x60
Tightening torque for cap bolts	80 N·m
Initial grease fill, 20%	80 g
Initial grease fill, 40%	135 g

Included products	
Пресс-маслёнка	АН 1/8-27 PTF

Свойства	
Тип корпуса	Plummer/pillow block
Housing configuration	Two-piece
Способ монтажа	Through shaft/Shaft end
Число отверстий под болты	2
Материал корпуса	Чугун
Bearing housing seal type	Без
Housing lubrication feature/possibility	Пластичная (консистентная)

Логистика	
Масса нетто	5.26 kg
Код eClass	23-05-17-01
Код UNSPSC	31171519





