



SKF 31320 X

Single row tapered roller bearing

Single row tapered roller bearings are designed to accommodate combined radial and axial loads and provide low friction during operation. The inner ring, with rollers and cage, can be mounted separately from the outer ring. These separable and interchangeable components facilitate mounting, dismounting and maintenance. By mounting one single row tapered roller bearing against another and applying a preload, a rigid bearing application can be achieved.

Technical specifications

General	
Dimension series	7GB
Dimensions	
Bore diameter	100 mm
Outside diameter	215 mm
Bearing width, total	56.5 mm
Shoulder diameter of inner ring	158.61 mm
Width of inner ring	51 mm
Width of outer ring	35 mm
Chamfer dimension of inner ring	4 mm
Chamfer dimension of outer ring	3 mm
Distance side face to pressure point	64.953 mm
Width, total	56.5 mm
Width, inner ring	51 mm
Width, outer ring	35 mm
Contact angle	28.8 °
Abutment dimensions	
Diameter of shaft abutment	121 mm
Diameter of shaft abutment	116 mm
Diameter of housing abutment	168 mm
Diameter of housing abutment	202.5 mm
Diameter of housing abutment	202 mm
Minimum width of space required in housing on large side face	7 mm
Minimum width of space required in housing on small side face	21.5 mm
Radius of shaft fillet	4 mm
Radius of housing fillet	3 mm
Calculation data	
Basic dynamic load rating	399 kN
Basic static load rating	465 kN
Fatigue load limit	51 kN
Reference speed	2200 r/min
Limiting speed	3000 r/min
Limiting value	0.83
Calculation factor	0.72
Calculation factor	0.4
Performance	
Basic dynamic load rating	399 kN
Basic static load rating	465 kN
Reference speed	2200 r/min
Limiting speed	3000 r/min
Properties	
Bearing part	Complete bearing
Number of rows	1

Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Sheet metal
Arrangement of contact angle (double-row bearing)	Not applicable
Matched arrangement	No
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Unit system	Metric
Indicative carbon footprint for new product	31 kg CO ₂ e

Logistics	
Product net weight	8.61 kg
eClass code	23-05-09-10
UNSPSC code	31171516

SKF drawings

