



SKF GEZ 300 ES

Radial spherical plain bearing, requiring maintenance, inch sizes

Radial spherical plain bearings are designed to accommodate radial and combined radial and axial loads, and also misalignment. This specific design includes a steel/steel sliding contact surface combination. The bearings require maintenance and can be relubricated via lubrication holes and an annular groove in both rings.

Technical specifications

General	
Maintenance	Relubrication required
Sliding contact surface combination	Steel/steel, standard
Material, inner ring	Bearing steel
Material, outer ring	Bearing steel
Sealing	Without
Dimensions	
Bore diameter	76.2 mm
Outside diameter	120.65 mm
Width	66.675 mm
Width outer ring	57.15 mm
Angle of tilt	6 °
Raceway diameter inner ring	109.525 mm
Width annular lubrication groove at outer ring	9.1 mm
Width annular lubrication groove at inner ring	8 mm
Diameter lubrication hole (outer ring)	6.5 mm
Chamfer dimension bore	0.6 mm
Chamfer dimension outer ring	1 mm
Width, inner ring	66.675 mm
Width, outer ring	57.15 mm
Abutment dimensions	
Abutment diameter shaft	81.4 mm
Abutment diameter shaft	86.9 mm
Abutment diameter housing	104 mm
Abutment diameter housing	115 mm
Fillet radius shaft	0.6 mm
Fillet radius housing	1 mm
Calculation data	
Basic dynamic load rating	500 kN
Basic static load rating	1500 kN
Specific dynamic load factor	100 N/mm ²
Specific static load factor	300 N/mm ²
Material constant	330
Performance	
Basic dynamic load rating	500 kN
Basic static load rating	1500 kN
Properties	
Sliding contact surface combination	Steel/steel, standard
Material, inner ring	Bearing steel
Material, outer ring	Bearing steel
Maintenance	Relubrication required
Radial internal clearance	CN
Sealing	Without

Relubrication feature	With
-----------------------	------

Logistics	
Product net weight	3.03 kg
eClass code	23-05-01-06
UNSPSC code	31171515

