



## SKF EEB 3-2Z

### Deep groove ball bearing with seals or shields

Single row deep groove ball bearings with seals or shields are particularly versatile, have low friction and are optimized for low noise and low vibration, which enables high rotational speeds. They accommodate radial and axial loads in both directions, are easy to mount, and require less maintenance than many other bearing types. The integral sealing can significantly prolong bearing service life because it keeps lubricant in the bearings and contaminants out.

## Technical specifications

Dimensions	
Bore diameter	9.525 mm
Outside diameter	22.225 mm
Width	7.144 mm

Performance	
Basic dynamic load rating	3.32 kN
Basic static load rating	1.4 kN
Reference speed	67000 r/min
Limiting speed	34000 r/min

Properties	
Filling slots	Without
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Sheet metal
Matched arrangement	No
Radial internal clearance	CN
Material, bearing	Bearing steel
Coating	Without
Sealing	Shield on both sides
Sealing type	Non-contact
Lubricant	Grease
Relubrication feature	Without
Indicative carbon footprint for new product	0.04 kg CO <sub>2</sub>

Logistics	
Product net weight	0.01 kg
eClass code	23-05-08-01
UNSPSC code	31171504