



SKF 99499

SKF Speedi-Sleeve

SKF Speedi-Sleeve provides an alternative to costly repairs for worn or damaged shafts. This thin-walled sleeve, specially developed by SKF, is simply positioned over the relevant part of the shaft and provides a smooth counterface that is optimized for radial shaft seals. Use of SKF Speedi-Sleeve can prevent the need for costly shaft treatments that may involve machining, hardening, plunge grinding or disassembly. SKF Speedi-Sleeve Gold is an enhanced version of standard SKF Speedi-Sleeve, offering improved resistance to abrasive wear.

Technical specifications

General	
Type	Standard
Dimensions	
Shaft diameter range	126.95 mm
Shaft diameter range	127.15 mm
Nominal bore diameter	127 mm
Nominal outside diameter	136.91 mm
Tolerance outside diameter D	1.57 mm
Nominal width	25.4 mm
Tolerance width b	0.8 mm
Nominal width of plain sleeve (up to flange groove)	20.65 mm
Tolerance width $b_{>1}$	0.8 mm
Installation distance	36.53 mm
Bushing radius (chamfer) between bore and side face	3.18 mm
Nominal thickness	0.25 mm
Width	25.4 mm
Shaft diameter, minimum	126.95 mm
Shaft diameter, maximum	127.15 mm
Shaft diameter	127 mm
Removable flange outside diameter	136.91 mm
Seal seat width	20.65 mm
Properties	
Type	Standard
Design	SSLV
Logistics	
Product net weight	0.24 kg
eClass code	23-05-92-90
UNSPSC code	31171605

SKF drawings

