



## SKF FYK 20 TR

Square flanged ball bearing unit with set screw locking and extended inner ring,

These square flanged ball bearing units are compliant with ISO standards. The unit consists of an insert bearing, with an extended inner ring and set screw locking, and is suitable for applications where the direction of rotation is constant or alternating. The bearing is mounted in a composite housing, which can be bolted to a machine wall or frame. Ball bearing units can accommodate moderate initial misalignment, but normally do not permit axial displacement.

### Technical specifications

General	
Compliance with standard	ISO
Purpose specific	For material handling applications
Material, housing	Composite
Sealing, bearing	Seal and flinger on both sides
Sealing type, bearing	Contact, multiple
Sealing, unit	Optional end cover
Coating	Without

Dimensions	
Bore diameter	20 mm
Outer diameter of inner ring	28.2 mm
Width of housing	30 mm
Flange width	15 mm
Depth of centring recess	3.2 mm
Standout of end cover	20 mm
Width of inner ring	31 mm
Overall bearing width	31 mm
Distance from locking device side face to thread centre	4.5 mm
Top external diameter	59 mm
Diameter of housing centering recess	68.3 mm
Centre distance between bolt holes	63.5 mm
Overall length	86 mm
Diameter of attachment bolt hole	12.3 mm
Distance from locking device side face to raceway centre	18.3 mm
Overall width	37.3 mm
Attachment bolt diameter	10 mm
Shaft diameter	20 mm
Housing overall width	30 mm
Bearing width, total	31 mm

Calculation data	
Basic dynamic load rating	12.7 kN
Basic static load rating	6.55 kN
Fatigue load limit	0.28 kN
Limiting speed	5000 r/min
	Limiting speed with shaft tolerance h6

Mounting information	
Set screw	M6x0.75
Hexagonal key size for set screw	3 mm
Recommended tightening torque for set screw	4 N·m
Recommended diameter for attachment bolts, mm	10 mm
Recommended diameter for attachment bolts, inch	0.375 in

Performance	
Basic dynamic load rating	12.7 kN
Basic static load rating	6.55 kN

Limiting speed	5000 r/min
Note	Limiting speed with shaft tolerance h6

<b>Properties</b>	
Housing type	Flanged
Flanged housing type	Square
Number of bolt holes for fasteners	4
Fastening bolt hole type	Plain
Retaining feature, inner ring	Set screws
Bore type	Cylindrical
Rubber seating ring	Without
Material, housing	Composite
Material, bearing	Bearing steel
Coating	Without
Sealing, bearing	Seal and flinger on both sides
Sealing type	Contact, multiple
Sealing, unit	Optional end cover
Lubricant	Grease
Relubrication hole	Without
Grease fitting	Without

<b>Logistics</b>	
Product net weight	0.266 kg
eClass code	23-05-08-02
UNSPSC code	31171536

**SKF drawings**

