



## SKF 6208/C3

### Deep groove ball bearing

Single row deep groove ball bearings are particularly versatile, have low friction and are optimized for low noise and low vibration, which enables high rotational speeds. They accommodate radial and axial loads in both directions, are easy to mount, and require less maintenance than many other bearing types.

## Technical specifications

| Dimensions       |       |
|------------------|-------|
| Bore diameter    | 40 mm |
| Outside diameter | 80 mm |
| Width            | 18 mm |

| Performance               |              |
|---------------------------|--------------|
| Basic dynamic load rating | 32.5 kN      |
| Basic static load rating  | 19 kN        |
| Reference speed           | 18000 r/min  |
| Limiting speed            | 11000 r/min  |
| SKF performance class     | SKF Explorer |

| Properties                                  |                          |
|---------------------------------------------|--------------------------|
| Filling slots                               | Without                  |
| Number of rows                              | 1                        |
| Locating feature, bearing outer ring        | Without                  |
| Bore type                                   | Cylindrical              |
| Cage                                        | Sheet metal              |
| Matched arrangement                         | No                       |
| Radial internal clearance                   | C3                       |
| Material, bearing                           | Bearing steel            |
| Coating                                     | Without                  |
| Sealing                                     | Without                  |
| Lubricant                                   | None                     |
| Relubrication feature                       | Without                  |
| Indicative carbon footprint for new product | 1.3 kg CO <sub>2</sub> e |

| Logistics          |             |
|--------------------|-------------|
| Product net weight | 0.352 kg    |
| eClass code        | 23-05-08-01 |
| UNSPSC code        | 31171504    |