



SKF 3201 A-2RS1TN9/MT33

Double row angular contact ball bearing with seals or shields

Double row angular contact ball bearings, with seals or shields, correspond to a pair of single row angular contact ball bearings in a back-to-back arrangement, while requiring less axial space. Depending on the sealing execution, they can operate at high speeds and are more suitable than deep groove ball bearings for supporting large axial forces in both directions.

Technical specifications

Dimensions	
Bore diameter	12 mm
Outside diameter	32 mm
Width	15.9 mm
Recess diameter inner ring shoulder	17.2 mm
Recess diameter outer ring shoulder	27.7 mm
Chamfer dimension inner ring	0.6 mm
Distance pressure point(s)	19 mm
Contact angle	30 °

Abutment dimensions	
Abutment diameter shaft	16.4 mm
Abutment diameter shaft	17 mm
Abutment diameter housing	27.6 mm
Fillet radius	0.6 mm

Calculation data	
Basic dynamic load rating	10.1 kN
Basic static load rating	5.6 kN
Fatigue load limit	0.24 kN
Limiting speed	15000 r/min
Calculation factor	0.06
Limiting value	0.8
Calculation factor	0.63
Calculation factor	0.66
Calculation factor	0.78
Calculation factor	1.2

Performance	
Basic dynamic load rating	10.1 kN
Basic static load rating	5.6 kN
Limiting speed	15000 r/min

Properties	
Contact type	Normal contact (two-point contact)
Number of rows	2
Locating feature, bearing outer ring	Without
Ring type	One-piece inner and outer rings
Cage	Non-metallic
Arrangement of contact angle (double-row bearing)	Back-to-back (O)
Matched arrangement	No
Universal matching bearing	No
Axial internal clearance	CN
Material, bearing	Bearing steel
Coating	Without
Sealing	Seal on both sides
Sealing type	Contact
Lubricant	Grease

Relubrication feature	Without
Indicative carbon footprint for new product	0.21 kg CO ₂ e

Logistics	
Product net weight	0.0583 kg
eClass code	23-05-08-03
UNSPSC code	31171531

SKF drawings

