



SKF 32032 X

Single row tapered roller bearing

Single row tapered roller bearings are designed to accommodate combined radial and axial loads and provide low friction during operation. The inner ring, with rollers and cage, can be mounted separately from the outer ring. These separable and interchangeable components facilitate mounting, dismounting and maintenance. By mounting one single row tapered roller bearing against another and applying a preload, a rigid bearing application can be achieved.

Technical specifications

General	
Dimension series	4EC

Dimensions	
Bore diameter	160 mm
Outside diameter	240 mm
Bearing width, total	51 mm
Shoulder diameter of inner ring	200.66 mm
Width of inner ring	51 mm
Width of outer ring	38 mm
Chamfer dimension of inner ring	3 mm
Chamfer dimension of outer ring	2.5 mm
Distance side face to pressure point	51.9 mm
Width, total	51 mm
Width, inner ring	51 mm
Width, outer ring	38 mm
Contact angle	17 °

Abutment dimensions	
Diameter of shaft abutment	176 mm
Diameter of shaft abutment	175 mm
Diameter of housing abutment	213 mm
Diameter of housing abutment	227.5 mm
Diameter of housing abutment	231 mm
Minimum width of space required in housing on large side face	8 mm
Minimum width of space required in housing on small side face	13 mm
Radius of shaft fillet	3 mm
Radius of housing fillet	2.5 mm

Calculation data	
SKF performance class	SKF Explorer
Basic dynamic load rating	532 kN
Basic static load rating	780 kN
Fatigue load limit	76.5 kN
Reference speed	2000 r/min
Limiting speed	2400 r/min
Limiting value	0.46
Calculation factor	1.3
Calculation factor	0.7

Performance	
Basic dynamic load rating	532 kN
Basic static load rating	780 kN
Reference speed	2000 r/min
Limiting speed	2400 r/min
SKF performance class	SKF Explorer

Properties	

Bearing part	Complete bearing
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Sheet metal
Arrangement of contact angle (double-row bearing)	Not applicable
Matched arrangement	No
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Unit system	Metric
Indicative carbon footprint for new product	28.2 kg CO ₂ e

Logistics	
Product net weight	7.83 kg
eClass code	23-05-09-10
UNSPSC code	31171516

SKF drawings