



SKF 61913

Deep groove ball bearing

Single row deep groove ball bearings are particularly versatile, have low friction and are optimized for low noise and low vibration, which enables high rotational speeds. They accommodate radial and axial loads in both directions, are easy to mount, and require less maintenance than many other bearing types.

Technical specifications

Dimensions	
Bore diameter	65 mm
Deviation limits of mid-range bore diameter	-0.012..0 mm
Outside diameter	90 mm
Deviation limits of mid-range outside diameter	-0.013..0 mm
Width	13 mm
Deviation limits of ring width	-0.15..0 mm
Shoulder diameter	73.3 mm
Shoulder diameter	82.3 mm
Recess diameter	84.2 mm
Chamfer dimension	1 mm
ISO tolerance class for dimensions	P6

Abutment dimensions	
Diameter of shaft abutment	69.6 mm
Diameter of housing abutment	85.4 mm
Radius of shaft or housing fillet	1 mm

Calculation data	
Basic dynamic load rating	17.4 kN
Basic static load rating	13.4 kN
Fatigue load limit	0.68 kN
Reference speed	15000 r/min
Limiting speed	9500 r/min
Minimum load factor	0.02
Calculation factor	13.8

Tolerances of run-out	
Range of section height at inner ring of assembled bearing	10 µm
Range of section height at outer ring of assembled bearing	18 µm
ISO tolerance class for geometrical tolerances	P6

Performance	
Basic dynamic load rating	17.4 kN
Basic static load rating	13.4 kN
Reference speed	15000 r/min
Limiting speed	9500 r/min

Properties	
Filling slots	Without
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Sheet metal
Matched arrangement	No
Radial internal clearance	CN
Material, bearing	Bearing steel
Coating	Without

Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	0.76 kg CO ₂ e

Logistics	
Product net weight	0.212 kg
eClass code	23-05-08-01
UNSPSC code	31171504

SKF drawings

