



SKF NA 2202.2RS

Support roller (yoke-type track roller), without flange rings, with integral sealing

Support rollers (yoke-type track rollers) are designed to run on all types of tracks and to be used in cam drives, conveyor systems, etc. They are based on a single row needle roller bearing with an inner ring and have a thick-walled outer ring with a crowned running surface. They are supplied sealed and are ready-to-mount. The inner ring contains a lubrication hole to facilitate relubrication. The inner ring can be mounted separately from the outer ring and roller and cage assembly.

Technical specifications

Dimensions	
Outside diameter	35 mm
Bore diameter	15 mm
Width outer ring	13.8 mm
Width inner ring	14 mm
Recess diameter outer ring shoulder	26 mm
Raceway diameter inner ring	20 mm
Chamfer dimension outer ring	0.6 mm
Chamfer dimension inner ring	0.3 mm
Functional outside diameter	35 mm
Width, total	14 mm
Width, outer ring	13.8 mm

Calculation data	
Basic dynamic load rating	7.48 kN
Basic static load rating	9.3 kN
Fatigue load limit	1.12 kN
Maximum dynamic radial load	9.5 kN
Maximum static radial load	13.7 kN
Limiting speed	5000 r/min

Performance	
Basic dynamic load rating	7.48 kN
Basic static load rating	9.3 kN
Limiting speed	5000 r/min

Properties	
Bearing part	Complete track roller
Rolling elements	Needle rollers
Number of rows	1
Outer ring profile	Crowned
Axial guidance of outer ring	Yes
Number of flanges, outer ring	2
Cage	With
Radial internal clearance	CN
Tolerance class	Other
Material, bearing	Bearing steel
Coating	Without
Sealing	Seal on both sides
Sealing type	Contact
Lubricant	Grease
Relubrication feature	With

Logistics	
Product net weight	0.075 kg
eClass code	23-05-09-03
UNSPSC code	31171512

SKF drawings

