



## SKF 2209 ETN9

### Self-aligning ball bearing

Self-aligning ball bearings have two rows of balls, a common sphered raceway in the outer ring and two deep uninterrupted raceway grooves in the inner ring. They are insensitive to angular misalignment of the shaft relative to the housing, which can be caused, for example, by shaft deflection.

## Technical specifications

Bore type	Cylindrical
<b>Dimensions</b>	
Bore diameter	45 mm
Outside diameter	85 mm
Width	23 mm
Shoulder diameter inner ring	55.32 mm
Shoulder diameter outer ring	73.2 mm
Chamfer dimension	1.1 mm
<b>Abutment dimensions</b>	
Abutment diameter shaft	52 mm
Abutment diameter housing	78 mm
Fillet radius	1.1 mm
<b>Calculation data</b>	
Basic dynamic load rating	32.5 kN
Basic static load rating	10.6 kN
Fatigue load limit	0.54 kN
Reference speed	15000 r/min
Limiting speed	10000 r/min
Permissible angular misalignment	2.5 °
Calculation factor	0.05
Limiting value	0.26
Calculation factor	2.5
Calculation factor	2.4
Calculation factor	3.7
<b>Performance</b>	
Basic dynamic load rating	32.5 kN
Basic static load rating	10.6 kN
Reference speed	15000 r/min
Limiting speed	10000 r/min
<b>Properties</b>	
Retaining feature, inner ring	None
Locating feature, bearing outer ring	Without
Number of rows	2
Bore type	Cylindrical
Cage	Non-metallic
Radial internal clearance	CN
Tolerance class	Normal
Material, bearing	Bearing steel
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without

Indicative carbon footprint for new product

1.9 kg CO<sub>2</sub>e

<b>Logistics</b>	
Product net weight	0.533 kg
eClass code	23-05-08-06
UNSPSC code	31171532

**SKF drawings**