



SKF 3200 ATN9

Double row angular contact ball bearing

Double row angular contact ball bearings correspond, in their design and operation, to a pair of single row angular contact ball bearings in a back-to-back arrangement, while requiring less axial space. They can operate at high speeds and are more suitable than deep groove ball bearings for supporting large axial forces in both directions.

Technical specifications

Dimensions	
Bore diameter	10 mm
Outside diameter	30 mm
Width	14 mm
Recess diameter inner ring shoulder	15.8 mm
Recess diameter outer ring shoulder	24.95 mm
Chamfer dimension inner ring	0.6 mm
Distance pressure point(s)	16 mm
Contact angle	30 °

Abutment dimensions	
Abutment diameter shaft	14.4 mm
Abutment diameter housing	25.6 mm
Fillet radius	0.6 mm

Calculation data	
Basic dynamic load rating	7.61 kN
Basic static load rating	4.3 kN
Fatigue load limit	0.183 kN
Reference speed	26000 r/min
Limiting speed	24000 r/min
Calculation factor	0.06
Limiting value	0.8
Calculation factor	0.63
Calculation factor	0.66
Calculation factor	0.78
Calculation factor	1.2

Performance	
Basic dynamic load rating	7.61 kN
Basic static load rating	4.3 kN
Reference speed	26000 r/min
Limiting speed	24000 r/min

Properties	
Contact type	Normal contact (two-point contact)
Number of rows	2
Locating feature, bearing outer ring	Without
Ring type	One-piece inner and outer rings
Cage	Non-metallic
Arrangement of contact angle (double-row bearing)	Back-to-back (O)
Matched arrangement	No
Universal matching bearing	No
Axial internal clearance	CN
Material, bearing	Bearing steel
Coating	Without
Sealing	Without
Lubricant	None

Relubrication feature	Without
Indicative carbon footprint for new product	0.18 kg CO ₂ e

Logistics	
Product net weight	0.0489 kg
eClass code	23-05-08-03
UNSPSC code	31171531

SKF drawings