



SKF 2318 M

Self-aligning ball bearing

Self-aligning ball bearings have two rows of balls, a common sphered raceway in the outer ring and two deep uninterrupted raceway grooves in the inner ring. They are insensitive to angular misalignment of the shaft relative to the housing, which can be caused, for example, by shaft deflection.

Technical specifications

Bore type	Cylindrical
Dimensions	
Bore diameter	90 mm
Outside diameter	190 mm
Width	64 mm
Shoulder diameter inner ring	121 mm
Shoulder diameter outer ring	162.2 mm
Chamfer dimension	3 mm
Abutment dimensions	
Abutment diameter shaft	104 mm
Abutment diameter housing	176 mm
Fillet radius	3 mm
Calculation data	
Basic dynamic load rating	151 kN
Basic static load rating	57 kN
Fatigue load limit	2.5 kN
Reference speed	6300 r/min
Limiting speed	4500 r/min
Permissible angular misalignment	3 °
Calculation factor	0.05
Limiting value	0.37
Calculation factor	1.8
Calculation factor	1.7
Calculation factor	2.6
Performance	
Basic dynamic load rating	151 kN
Basic static load rating	57 kN
Reference speed	6300 r/min
Limiting speed	4500 r/min
Properties	
Retaining feature, inner ring	None
Locating feature, bearing outer ring	Without
Number of rows	2
Bore type	Cylindrical
Cage	Machined brass
Radial internal clearance	CN
Tolerance class	Normal
Material, bearing	Bearing steel
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without

Indicative carbon footprint for new product

30.8 kg CO₂e

Logistics

Product net weight

8.55 kg

eClass code

23-05-08-06

UNSPSC code

31171532

SKF drawings