



## SKF 3307 ATN9

### Double row angular contact ball bearing

Double row angular contact ball bearings correspond, in their design and operation, to a pair of single row angular contact ball bearings in a back-to-back arrangement, while requiring less axial space. They can operate at high speeds and are more suitable than deep groove ball bearings for supporting large axial forces in both directions.

## Technical specifications

Dimensions	
Bore diameter	35 mm
Outside diameter	80 mm
Width	34.9 mm
Recess diameter inner ring shoulder	44.6 mm
Recess diameter outer ring shoulder	70.5 mm
Chamfer dimension inner ring	1.5 mm
Distance pressure point(s)	47 mm
Contact angle	30 °

Abutment dimensions	
Abutment diameter shaft	44 mm
Abutment diameter housing	71 mm
Fillet radius	1.5 mm

Calculation data	
SKF performance class	SKF Explorer
Basic dynamic load rating	54 kN
Basic static load rating	38 kN
Fatigue load limit	1.63 kN
Reference speed	8500 r/min
Limiting speed	8500 r/min
Calculation factor	0.07
Limiting value	0.8
Calculation factor	0.63
Calculation factor	0.66
Calculation factor	0.78
Calculation factor	1.2

Performance	
Basic dynamic load rating	54 kN
Basic static load rating	38 kN
Reference speed	8500 r/min
Limiting speed	8500 r/min
SKF performance class	SKF Explorer

Properties	
Contact type	Normal contact (two-point contact)
Number of rows	2
Locating feature, bearing outer ring	Without
Ring type	One-piece inner and outer rings
Cage	Non-metallic
Arrangement of contact angle (double-row bearing)	Back-to-back (O)
Matched arrangement	No
Universal matching bearing	No
Axial internal clearance	CN
Material, bearing	Bearing steel
Coating	Without

Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	2.5 kg CO <sub>2</sub> e

<b>Logistics</b>	
Product net weight	0.704 kg
eClass code	23-05-08-03
UNSPSC code	31171531

**SKF drawings**

