



## SKF LAGF 18

### Grease filler pump for use on drums

Best lubrication practices say that each type of grease requires an individual grease gun and that the refilling has to be a clean process. SKF Grease Filler Pumps are designed to achieve this goal. The LAGF 18 is operated with a mechanical lever and enables optimum cleanliness for filling grease guns from a 18 kg drum.

## Technical specifications

| Dimensions                        |                                                                                              |
|-----------------------------------|----------------------------------------------------------------------------------------------|
| Suitable drum inner diameter      | Array mm                                                                                     |
| Suitable drum inside height (max) | 420 mm                                                                                       |
| Performance                       |                                                                                              |
| Maximum pressure ( $P_{max}$ )    | 3 MPa                                                                                        |
| Properties                        |                                                                                              |
| Recommended applications          | grease filler pump for drums or pails designed to fill grease guns or TLRD grease dispensers |
| For type/size of grease drum      | 18 kg grease pails                                                                           |
| Operation                         | manual pump with handle                                                                      |
| Mobility                          | stationary                                                                                   |
| NLGI class of lubricant (max)     | 2                                                                                            |
| Connection                        | greasing point: DIN 1283 nipple                                                              |
| Air pressure                      | Array bar                                                                                    |
| Volume per stroke                 | 45 ml                                                                                        |
| Hose                              | No                                                                                           |
| Power source                      | manual                                                                                       |
| Material                          | steel                                                                                        |
| Material handle                   | steel with plastic grip                                                                      |
| Ambient temperature range         | Array °C                                                                                     |
| Recommended storage temperature   | Array °C                                                                                     |
| Relative humidity                 | < 65 %                                                                                       |
| Content                           | grease pump with pump handle, drum cover plate, drum followerplate                           |
| Logistics                         |                                                                                              |
| Product net weight                | 4.12 kg                                                                                      |
| eClass code                       | 23-06-91-06                                                                                  |
| UNSPSC code                       | 15121902                                                                                     |