



SKF 99595

SKF Speedi-Sleeve

SKF Speedi-Sleeve provides an alternative to costly repairs for worn or damaged shafts. This thin-walled sleeve, specially developed by SKF, is simply positioned over the relevant part of the shaft and provides a smooth counterface that is optimized for radial shaft seals. Use of SKF Speedi-Sleeve can prevent the need for costly shaft treatments that may involve machining, hardening, plunge grinding or disassembly. SKF Speedi-Sleeve Gold is an enhanced version of standard SKF Speedi-Sleeve, offering improved resistance to abrasive wear.

Technical specifications

General	
Type	Standard
Dimensions	
Shaft diameter range	149.76 mm
Shaft diameter range	150.01 mm
Nominal bore diameter	149.99 mm
Nominal outside diameter	159 mm
Tolerance outside diameter D	1.57 mm
Nominal width	30 mm
Tolerance width b	0.8 mm
Nominal width of plain sleeve (up to flange groove)	26.01 mm
Tolerance width $b_{>1}$	0.8 mm
Installation distance	32.51 mm
Bushing radius (chamfer) between bore and side face	3.18 mm
Nominal thickness	0.25 mm
Width	30 mm
Shaft diameter, minimum	149.76 mm
Shaft diameter, maximum	150.01 mm
Shaft diameter	149.99 mm
Removable flange outside diameter	159 mm
Seal seat width	26.01 mm
Properties	
Type	Standard
Design	SSLV
Logistics	
Product net weight	0.318 kg
eClass code	23-05-92-90
UNSPSC code	31171605

SKF drawings