



## SKF 29420 E

### Spherical roller thrust bearing with stamped steel cage

Spherical roller thrust bearings accommodate very heavy axial and considerable radial loads. They have the highest load rating of all thrust bearings, enabling compact, high power density bearing arrangements. By combining two or more spherical roller thrust bearings, it is possible to create a bearing arrangement that is either self-aligning, allowing misalignment of the shaft, or very stiff.

## Technical specifications

Dimensions	
Bore diameter	100 mm
Outside diameter	210 mm
Height	67 mm
Outside diameter of shaft washer end side face	182 mm
Shoulder diameter outer ring	142 mm
Width shaft washer or length of shaft washer bore diameter that fits on shaft (bearings with a stamped steel cage)	43 mm
Height shaft washer + cage	57.3 mm
Height housing washer	32 mm
Distance from shaft washer end side face to pressure point	62 mm
Chamfer dimension shaft washer	3 mm

Abutment dimensions	
Diameter of shaft abutment	150 mm
Abutment diameter of spacer ring	110 mm
Outside diameter of spacer ring	110 mm
Diameter of housing abutment	175 mm
Fillet radius	2.5 mm

Calculation data	
Basic dynamic load rating	980 kN
Basic static load rating	2500 kN
Fatigue load limit	275 kN
Reference speed	1700 r/min
Limiting speed	3000 r/min
Minimum axial load factor	0.59

Performance	
Basic dynamic load rating	980 kN
Basic static load rating	2500 kN
Reference speed	1700 r/min
Limiting speed	3000 r/min
SKF performance class	SKF Explorer

Properties	
Locating feature, housing washer	None
Bore type	Cylindrical
Cage	Sheet metal
Tolerance class	Normal
Indicative carbon footprint for new product	36.4 kg CO <sub>2</sub>

Logistics	
Product net weight	10.1 kg
eClass code	23-05-11-03
UNSPSC code	31171507

**SKF drawings**

