



SKF NU 204 ECP

Single row cylindrical roller bearing, NU design

Single row cylindrical roller bearings are designed to accommodate high radial loads in combination with high speeds. Having two integral flanges on the outer ring and no flanges on the inner ring, NU design bearings can accommodate axial displacement in both directions. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.

Technical specifications

Dimensions	
Bore diameter	20 mm
Outside diameter	47 mm
Width	14 mm
Shoulder diameter of outer ring	38.44 mm
Raceway diameter of inner ring	26.5 mm
Chamfer dimension	1 mm
Chamfer dimension	0.6 mm
Permissible axial displacement	1 mm

Abutment dimensions	
Diameter of spacer sleeve	24 mm
Diameter of spacer sleeve	25.4 mm
Diameter of shaft abutment	28 mm
Diameter of housing abutment	41.7 mm
Radius of fillet	1 mm
Radius of fillet	0.6 mm

Calculation data	
SKF performance class	SKF Explorer
Basic dynamic load rating	28.5 kN
Basic static load rating	22 kN
Fatigue load limit	2.75 kN
Reference speed	17000 r/min
Limiting speed	19000 r/min
Minimum load factor	0.15
Limiting value	0.2
Calculation factor	0.6

Performance	
Basic dynamic load rating	28.5 kN
Basic static load rating	22 kN
Reference speed	17000 r/min
Limiting speed	19000 r/min
SKF performance class	SKF Explorer

Properties	
Bearing part	Complete bearing
Axial displacement capability	In both directions
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Non-metallic
Number of flanges, outer ring	2
Number of flanges, inner ring	0
Loose flange	None
Radial internal clearance	CN
Tolerance class	Normal

Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	0.39 kg CO ₂ e

Logistics	
Product net weight	0.109 kg
eClass code	23-05-09-01
UNSPSC code	31171505

SKF drawings