



SKF 23264 CC/W33

Spherical roller bearing with relubrication features

Spherical roller bearings can accommodate heavy loads in both directions. They are self-aligning and accommodate misalignment and shaft deflections, with virtually no increase in friction or temperature. The design includes features to facilitate relubrication. The bearings can be used in a modular system, including housings, sleeves and nuts.

Technical specifications

General	
Bore type	Cylindrical

Dimensions	
Bore diameter	320 mm
Deviation limits of mid-range bore diameter	-0.04..0 mm
Outside diameter	580 mm
Deviation limits of mid-range outside diameter	-0.05..0 mm
Width	208 mm
Deviation limits of ring width	-0.4..0 mm
Shoulder diameter of inner ring	382 mm
Shoulder/recess diameter of outer ring	493 mm
Width of lubrication groove	22.3 mm
Diameter of lubrication hole	12 mm
Chamfer dimension	5 mm
ISO tolerance class for dimensions	Normal

Abutment dimensions	
Diameter of shaft abutment	340 mm
Diameter of housing abutment	560 mm
Radius of fillet	4 mm

Calculation data	
SKF performance class	SKF Explorer
Basic dynamic load rating	4607 kN
Basic static load rating	6700 kN
Fatigue load limit	475 kN
Reference speed	700 r/min
Limiting speed	950 r/min
Limiting value	0.35
Calculation factor	1.9
Calculation factor	2.9
Calculation factor	1.8

Tolerances of run-out	
Range of section height at inner ring of assembled bearing	60 µm
Range of section height at outer ring of assembled bearing	100 µm
ISO tolerance class for geometrical tolerances	Normal

Radial internal clearance	
Minimum initial clearance	200 µm
Maximum initial clearance	310 µm

Performance	
Basic dynamic load rating	4607 kN
Basic static load rating	6700 kN
Reference speed	700 r/min
Limiting speed	950 r/min

Properties	
Number of rows	2
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Sheet metal
Radial internal clearance	CN
Tolerance class for dimensions	Normal
Tolerance class for run-out	Normal
Sealing	Without
Lubricant	None
Relubrication feature	With
Candidate for remanufacturing	Yes
Indicative carbon footprint for new product	847 kg CO ₂ e
Indicative carbon footprint for remanufactured product	296 kg CO ₂ e

Logistics	
Product net weight	235 kg
eClass code	23-05-09-11
UNSPSC code	31171510

