

# SKF TMFS 16

## Axial lock nut socket

The TMFS axial lock nut sockets are used to mount bearings on tapered journals or adapter sleeves and for dismounting bearings on withdrawal sleeves. Available in 21 different sizes, they are suitable for various locknuts sizes 0 to 20.

### Technical specifications

Dimensions	
Locknut size	Array
Outer diameter lock nut (range) (d <sub>3</sub> )	Array mm
Drive connection (C)	1"
Height (H)	110 mm
Effective height (h)	80 mm
Outer diameter (d <sub>3</sub> )	116 mm

Properties	
Recommended applications	For a controlled use with torque wrenches or power tools for safe tightening or loosening of lock nuts on shafts, adapter sleeves, and withdrawal sleeves or in blind housings. Also particularly suitable for applications where space limitations prevent the use of hookspanners.
Series	Axial lock nut socket, TMFS
Type	Model A
Allows bearing mounting	No
Fits on lock nuts inside SKF split pillow block housings (SNL)	No
Suitable SKF Locknut	KM 16, KMFE 16, KMK 16
Material	Alloy engineering steel, hardened and tempered
Coating	Black oxide
Colour	Metallic Black

Logistics	
Product net weight	1.77 kg
eClass code	23-05-19-01
UNSPSC code	27111712