



SKF W 6206

Stainless steel deep groove ball bearing

Stainless steel single row deep groove ball bearings provide greater chemical and corrosion resistance. As with deep groove ball bearings generally, they are particularly versatile, have low friction and are optimized for low noise and low vibration, which enables high rotational speeds. They accommodate radial and axial loads in both directions, are easy to mount, and require less maintenance than many other bearing types.

Technical specifications

Dimensions	
Bore diameter	30 mm
Outside diameter	62 mm
Width	16 mm
Shoulder diameter	40.7 mm
Recess diameter	55.13 mm
Chamfer dimension	1 mm

Abutment dimensions	
Diameter of shaft abutment	35 mm
Diameter of housing abutment	57 mm
Radius of shaft or housing fillet	1 mm

Calculation data	
Basic dynamic load rating	16.5 kN
Basic static load rating	11.2 kN
Fatigue load limit	0.48 kN
Reference speed	26000 r/min
Limiting speed	16000 r/min
Minimum load factor	0.03
Calculation factor	13.9

Performance	
Basic dynamic load rating	16.5 kN
Basic static load rating	11.2 kN
Reference speed	26000 r/min
Limiting speed	16000 r/min

Properties	
Filling slots	Without
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Stamped stainless steel
Matched arrangement	No
Radial internal clearance	CN
Material, bearing	Stainless steel
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	0.67 kg CO ₂

Logistics	
Product net weight	0.185 kg
eClass code	23-05-08-01
UNSPSC code	31171504

SKF drawings