



SKF KRV 26 PPXA

Cam follower (stud-type track roller) with integral sealing and relubrication feature

Cam followers (stud-type track rollers) are designed to run on all types of tracks and to be used in cam drives, conveyor systems, etc. They are based on a needle roller bearing with a threaded solid stud instead of an inner ring. They have a thick-walled outer ring with a cylindrical running surface and are supplied sealed and ready-to-mount. The bearings can be relubricated via the stud.

Technical specifications

Dimensions	
Outside diameter	26 mm
Attachment diameter	10 mm
Total length	36 mm
Width outer ring	12 mm
Length shank on stud	23 mm
Distance face outer ring to face side washer	0.6 mm
Outside diameter flange ring	17.1 mm
Thread stud	M 10x1
Length thread	12 mm
Seat diameter for lubrication accessories	4 mm
Width across flats	5 mm
Chamfer dimension	0.3 mm
Functional outside diameter	26 mm
Stud diameter	10 mm
Length	36 mm
Width, outer ring	12 mm
Calculation data	
Basic dynamic load rating	6.82 kN
Basic static load rating	11 kN
Fatigue load limit	1.25 kN
Maximum dynamic radial loads	11.4 kN
Maximum static radial loads	16.3 kN
Limiting speed	3600 r/min
Mounting information	
Recommended tightening torque	15 N·m
Included products	
Grease fitting	NIP A1x4.5
Hexagonal nut	M 10x1
Performance	
Basic dynamic load rating	6.82 kN
Basic static load rating	11 kN
Limiting speed	3600 r/min
Properties	
Rolling elements	Needle rollers
Number of rows	1
Outer ring profile	Cylindrical
Stud alignment	Centric
Number of flanges, outer ring	2
Feature for tightening	Hexagonal recess
Cage	Without
Radial internal clearance	Between C2 and CN
Tolerance class	Other

Material, bearing	Bearing steel
Coating	Without
Sealing	Seal on both sides
Sealing type	Labyrinth
Lubricant	Grease
Relubrication feature	Centre of each stud end

Logistics	
Product net weight	0.061 kg
eClass code	23-05-09-03
UNSPSC code	31171512

SKF drawings

