

SKF HN 5-6

Hook spanner

The SKF Hook spanner, size 5 - 6, is designed for easy tightening and loosening of lock nuts. They are used to secure and adjust bearings on tapered journals, adapter sleeves and withdrawal sleeves. They fit on a variety of lock nuts with outer diameter(s) 38 - 45 mm. To be more specific for locknuts: KM 5, KM 6, KMK 5, KMK 6, KMFE 5, KMFE 6, KMT 3, KMT 4, KMT 5, N 05, N 06 and M22x1,5, M24x1,5, M26x1,5 (DIN 1804).

Technical specifications

Dimensions	
Locknut size	Array
Outer diameter lock nut (range) (d ₃)	Array mm
Nose width (N _k)	5 mm
Nose height (N _h)	3 mm
Thickness (n)	5 mm
Length (L)	174 mm
Working length (l)	150 mm
Height (H)	31 mm

Properties	
Recommended applications	For applications that require tightening/loosening a wide variety of lock nuts on shafts, adapter sleeves, and withdrawal sleeves.
Series	Hook spanner, standard, HN
Type	Model B
Allows bearing mounting	Yes, angle method or with clearance reduction measurement
Size according DIN 1810	-
Fits on lock nuts inside SKF split pillow block housings (SNL)	No
Suitable SKF Locknut	KM 5, KM 6, KMFE 5, KMFE 6, KMK 5, KMK 6, KMT 3, KMT 4, KMT 5, N 05, N 06
Material	Medium carbon steel, hardened and tempered
Material handle	Durable soft plastic
Coating	Black phosphated
Colour	Black, with red handle
Part of a kit	Yes, HN 4-16/SET

Logistics	
Product net weight	0.09 kg
eClass code	23-05-19-01
UNSPSC code	27111712