



SKF NU 322 ECP

Single row cylindrical roller bearing, NU design

Single row cylindrical roller bearings are designed to accommodate high radial loads in combination with high speeds. Having two integral flanges on the outer ring and no flanges on the inner ring, NU design bearings can accommodate axial displacement in both directions. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.

Technical specifications

Dimensions	
Bore diameter	110 mm
Outside diameter	240 mm
Width	50 mm
Shoulder diameter of outer ring	200.05 mm
Raceway diameter of inner ring	143 mm
Chamfer dimension	3 mm
Chamfer dimension	3 mm
Permissible axial displacement	3 mm

Abutment dimensions	
Diameter of spacer sleeve	124 mm
Diameter of spacer sleeve	139 mm
Diameter of shaft abutment	146 mm
Diameter of housing abutment	225.2 mm
Radius of fillet	2.5 mm
Radius of fillet	2.5 mm

Calculation data	
SKF performance class	SKF Explorer
Basic dynamic load rating	530 kN
Basic static load rating	540 kN
Fatigue load limit	61 kN
Reference speed	3000 r/min
Limiting speed	3400 r/min
Minimum load factor	0.15
Limiting value	0.2
Calculation factor	0.6

Associated products	
Angle ring	HJ 322 EC

Performance	
Basic dynamic load rating	530 kN
Basic static load rating	540 kN
Reference speed	3000 r/min
Limiting speed	3400 r/min
SKF performance class	SKF Explorer

Properties	
Bearing part	Complete bearing
Axial displacement capability	In both directions
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Non-metallic
Number of flanges, outer ring	2
Number of flanges, inner ring	0

Loose flange	None
Radial internal clearance	CN
Tolerance class	Normal
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	36.9 kg CO ₂ e

Logistics	
Product net weight	10.3 kg
eClass code	23-05-09-01
UNSPSC code	31171505

SKF drawings