

SKF HNA 14-24

Adjustable hook spanner



The SKF Adjustable hook spanner, size 14 - 24, has a pivoting hook that allows tightening and loosening of a variety of lock nuts. They are used to secure and adjust bearings on tapered journals, adapter sleeves and withdrawal sleeves. They are an economic solution as they fit on a variety of lock nuts with outer diameters 90 - 155 mm. To be more specific for locknuts: KM 14 - 24, KMK 14 - 24, KMFE 14 - 24, KMT 13 - 24, N 14 and M62x1,5 - M110x2 (DIN 1804)

Technical specifications

Dimensions	
Locknut size	Array
Outer diameter lock nut (range) (d ₃)	Array mm
Nose width (N _k)	12 mm
Nose height (N _h)	5.5 mm
Thickness (n)	12 mm
Length (L)	332 mm
Working length (l)	275 mm
Height (H)	83 mm

Properties	
Recommended applications	A versatile tool, covering multiple lock nut sizes, when working with of lock nuts on shafts, adapter sleeves, and withdrawal sleeves in various applications.
Series	Hook spanner, adjustable, HN A
Type	Model C
Allows bearing mounting	No
Fits on lock nuts inside SKF split pillow block housings (SNL)	No
Suitable SKF Locknut	KM 14, KM 15, KM 16, KM 17, KM 18, KM 19, KM 20, KM 22, KM 24, KMF 14, KMF 15, KMF 16, KMF 17, KMF 18, KMF 19, KMF 19, KMF 20, KMFE 14, KMFE 15, KMFE 15 H, KMFE 16, KMFE 17, KMFE 18, KMFE 19, KMFE 20, KMFE 21, KMFE 22, KMFE 24, KMK 13, KMK 15, KMK 16, KMK 17, KMK 18, KMK 19, KMK 20, KML 24, KML 26, KMT 13, KMT 14, KMT 15, KMT 16, KMT 17, KMT 18, KMT 19, KMT 20, KMT 20, KMT 22, KMT 24, KMT 24, N 14, N 15, N 16, N 17, N 18, N 19, N 20, N 21, N 22, N 24, N 022, N 024, AN 15, AN 16, AN 17, AN 18, AN 19, AN 20, AN 21, AN 22, AN 24
Material	Medium carbon steel, hardened and tempered
Material handle	Durable soft plastic
Coating	Black oxide
Colour	Black, with blue handle

Logistics	
Product net weight	0.6 kg
eClass code	23-05-19-01
UNSPSC code	27111712