



SKF NA 6908

Double row needle roller bearing with machined rings, with flanges and an inner

Double row needle roller bearings incorporate cylindrical rollers that are small in diameter relative to their length. Owing to their large number of rollers, the bearings have a high load carrying capacity. The outer ring includes flanges to guide the roller and cage assemblies and has features to facilitate relubrication. It is possible to assemble the inner and outer rings separately, permitting interference fits for shaft and housing and enabling easy maintenance inspections.

Technical specifications

Dimensions	
Bore diameter	40 mm
Outside diameter	62 mm
Width	40 mm
Raceway diameter inner ring	48 mm
Chamfer dimension outer ring	0.6 mm
Permissible axial displacement from the normal position of one bearing ring relative to the other	0.5 mm

Abutment dimensions	
Smallest permissible abutment diameter shaft, bearings with flanges	44 mm
Diameter of housing abutment	58 mm
Fillet radius	0.6 mm

Calculation data	
SKF performance class	SKF Explorer
Basic dynamic load rating	76.5 kN
Basic static load rating	125 kN
Fatigue load limit	16 kN
Reference speed	8000 r/min
Limiting speed	9500 r/min

Performance	
Basic dynamic load rating	76.5 kN
Basic static load rating	125 kN
Reference speed	8000 r/min
Limiting speed	9500 r/min
SKF performance class	SKF Explorer

Properties	
Bearing part	Complete bearing
Number of rows	2
Outer ring type	Machined (solid)
Aligning feature	Without
Cage	Sheet metal
Number of flanges, outer ring	3
Radial internal clearance	CN
Tolerance class	Normal
Material, bearing	Bearing steel
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	With
Indicative carbon footprint for new product	1.6 kg CO ₂

Logistics	
Product net weight	0.43 kg

eClass code	23-05-09-03
UNSPSC code	31171512

SKF drawings

