

SKF HN 8/SNL

Hook spanner for use inside split plummer (pillow) block housings

The unique protected design of this SKF Hook spanner, allows it to tighten and loosen lock nuts whilst these are inside SKF split plummer (pillow) block housings (SNL). Alternatively it can be used as regular hook spanner. They are used to secure and adjust bearings on tapered journals, adapter sleeves and withdrawal sleeves. The SKF hook spanner HN 8/SNL, is designed for nuts with an outer diameter of 58 mm. In particular for lock nuts of series KM 8, KMK 8, KMFE 8, KMT , N 08 and M38x1,5 (DIN 1804).

Technical specifications

Dimensions	
Locknut size	Array
Outer diameter lock nut (range) (d ₃)	Array mm
Nose width (N _k)	7 mm
Nose height (N _h)	3 mm
Thickness (n)	7 mm
Length (L)	247 mm
Working length (l)	245 mm

Properties	
Recommended applications	Special designed tool for tightening/loosening lock nuts in split plummer (pillow) block housings, where space is the limiting factor. Alternative use is general bearing arrangements and of lock nuts on shafts, adapter sleeves, and withdrawal sleeves in a wide variety of applications.
Series	Hook spanner, for housings, HN SNL
Type	Model D
Allows bearing mounting	Yes, angle method or with clearance reduction measurement
Fits on lock nuts inside SKF split pillow block housings (SNL)	Yes
Suitable SKF Locknut	KM 8, KMFE 8, KMK 8, N 08
Material	Medium carbon steel, hardened and tempered
Material handle	Steel
Coating	Black phosphated
Colour	Black metallic

Logistics	
Product net weight	0.28 kg
eClass code	23-05-19-01
UNSPSC code	27111712