



SKF NK 60/25 TN

Single row needle roller bearing with machined rings, with flanges, without inner

Single row needle roller bearings without an inner ring consist of an outer ring with a needle roller and cage assembly. They are an excellent choice for compact bearing arrangements in applications where hardened and ground raceways can be provided on the shaft. The outer ring includes two integral flanges to guide the bearing axially and an annular groove with one or more lubrication holes to facilitate relubrication.

Technical specifications

Dimensions	
Diameter under rollers	60 mm
Outside diameter	72 mm
Width	25 mm
Chamfer dimension outer ring	0.6 mm
Bore diameter of needle roller complement	60 mm

Abutment dimensions	
Diameter of housing abutment	68 mm
Fillet radius	0.6 mm

Calculation data	
Basic dynamic load rating	46.8 kN
Basic static load rating	110 kN
Fatigue load limit	13.4 kN
Reference speed	6700 r/min
Limiting speed	7500 r/min

Associated seals	
Radial shaft seal	60x72x8 HMS5 RG

Performance	
Basic dynamic load rating	46.8 kN
Basic static load rating	110 kN
Reference speed	6700 r/min
Limiting speed	7500 r/min

Properties	
Bearing part	Bearing without inner ring
Number of rows	1
Outer ring type	Machined (solid)
Aligning feature	Without
Cage	Non-metallic
Number of flanges, outer ring	2
Tolerance class	Normal
Material, bearing	Bearing steel
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	With
Indicative carbon footprint for new product	0.61 kg CO ₂

Logistics	
Product net weight	0.17 kg
eClass code	23-05-09-03
UNSPSC code	31171512

SKF drawings

