



SKF 110 VS V

V-ring seal, VS design, global standard, interchangeable with VR2 design

V-ring seals (V-rings) are all-rubber, axial shaft seals. They offer an easy-to-install solution for rotating shaft applications, including use as a secondary seal in highly contaminated environments. The VS design includes a standard low cross section with a tapered back side face and a wide seal body, providing a firm hold on the shaft. VS seals are commonly used in agricultural and automotive applications.

Technical specifications

General	
Design	VS
Lip material	Fluoro rubber (FKM)
Dimensions	
Shaft diameter range (over)	105 mm
Shaft diameter range (incl.)	115 mm
Seal inside diameter, free state	99 mm
Nominal seal width	18 mm
Seal seat width	13.1 mm
Nominal seal height	7 mm
Radial gap (twice)	4 mm
	$D_{₁ \text{ max.}} = d_{₁} + 2x$
Radial distance (twice)	21 mm
	$D_{\text{min.}} = d_{₁} + 2y$
Seal fitted width	15.5 mm
Shaft diameter, minimum	105 mm
Shaft diameter, maximum	115 mm
Seal width	18 mm
Application and operating conditions	
Operating temperature	-20 °C
Operating temperature	150 °C
Properties	
Design	VS
Sealing lip material	Fluoro rubber (FKM)
Logistics	
Product net weight	0.0573 kg
eClass code	23-07-08-01
UNSPSC code	31181602

SKF drawings