

SKF TММА 100Н

Инструмент SKF

Инструменты SKF для монтажа и демонтажа подшипников — ударные ключи, нагреватели, съёмники, гидравлические гайки. Обеспечивают безопасную и точную установку.

Характеристики

Размеры	
Width of grip external	Array mm
Effective arm length	250 mm
Claw height	13.8 mm
Claw length	24 mm
Total Arm length	416 mm
Claw width	40 mm
Hydraulic spindle, piston stroke	85 mm
Puller adaptor thread	UN 1.5 x 16 tpi
Total spindle length	655 mm

Свойства	
Рекомендуемые применения	For the dismounting of bearings, gears, pulleys and other industrial ring shaped components in industrial, construction and agricultural applications with an interference fit on the shaft
Suitable for workpiece dismounting from a Cylindrical seating (straight shaft)	Да
Suitable for bearing dismounting from a Tapered seating (conical shaft)	Да
Suitable for bearing dismounting from a Sleeve (adapter or withdrawal sleeve)	Да
Suitable for workpiece dismounting from a Blind arrangement (housing with shaft)	Нет
Suitable for workpiece dismounting from a Housing	Нет
Suitable for bearing type(s)	All
Dismounting force generation	Hydraulic spindle (TMHS 100)
Special features	Spring operated opening mechanism
Number of arms	3
Pulling force (max)	100 kN
Spindle nose piece	yes, ø 30mm
Цвет	Black, with red handle
Материал	Alloy engineering steels, hardened and tempered
Покрытие	Black phosphated, red powdercoated
Content	1x Puller TММА 100Н ; 1x Mounted hydraulic spindle TMHS 100; 3x Spindle extension pieces, 1x Nose piece, 1x Handle, 1x Handle rod;1x Printed instructions for use

Логистика	
Масса нетто	13.4 kg
Код eClass	23-05-19-01
Код UNSPSC	27111712