


SKF TMBP 20E

Инструмент SKF

Инструменты SKF для монтажа и демонтажа подшипников — ударные ключи, нагреватели, съёмники, гидравлические гайки. Обеспечивают безопасную и точную установку.



Характеристики

Размеры	
Total spindle length	328 mm
Case dimensions (l x h x w)	530 x 85 x 180 mm
Свойства	
Suitable for workpiece dismounting from a Cylindrical seating (straight shaft)	Да
Suitable for bearing dismounting from a Tapered seating (conical shaft)	Нет
Suitable for bearing dismounting from a Sleeve (adapter or withdrawal sleeve)	Нет
Suitable for workpiece dismounting from a Blind arrangement (housing with shaft)	Да
Suitable for workpiece dismounting from a Housing	Нет
Suitable for bearing type(s)	SKF Deep Groove Ball Bearings (DGBB's)
Bearing bore diameter range	Array mm
Number of arms	2
Number of arm extension pieces	4 included
Spindle torque (max)	155 N·m
Pulling force (max)	55 kN
Max bearing depth	With standard arm: 147 mm;With arm and 1 extension rod, 347 mm;With arm and 2 extension rods 547 mm
Total Arm length	Arm rod: 225 mm;Arm rod + extension rod: 425 mm;Arm rod + 2 extension rods: 625 mm
Effective spindle length	225 mm
Spindle nose piece	Yes , diameter 39mm
Spindle head, hexagon size	22 mm
Total number of bearing adapters in kit	6 sets of 2
Total number of spindles in kit	1
Материал	Medium carbon steels and alloy engineering steels, hardened and tempered
Покрытие	Black phosphated
Цвет	Black metallic
Content	6x sets of 2 bearing adapters, size A to F;1x Beam; 1x spindle with nose piece;2x arm rods;4x arm extension rods;4x washers;2x nuts;1x printed Instruction for Use (language free);1x Carrying case (size X)
Логистика	
Масса нетто	6.46 kg
Код eClass	23-05-19-01
Код UNSPSC	27111712