



SKF 11212 TN9

Self-aligning ball bearing with extended inner ring

Self-aligning ball bearings, with extended inner ring, have two rows of balls, a common sphered raceway in the outer ring and two deep uninterrupted raceway grooves in the inner ring. They are insensitive to angular misalignment of the shaft relative to the housing. The extended inner ring enables use of commercial grade shafting and axially location on the shaft by means of a slot at one end of the inner ring.

Technical specifications

Bore type	Cylindrical
Dimensions	
Bore diameter	60 mm
Outside diameter	110 mm
Width	62 mm
Width outer ring	22 mm
Shoulder diameter inner ring	78 mm
Shoulder diameter outer ring	95.6 mm
Chamfer dimension	1.5 mm
Abutment dimensions	
Abutment diameter housing	101 mm
Fillet radius	1.5 mm
Calculation data	
Basic dynamic load rating	31.2 kN
Basic static load rating	12.2 kN
Fatigue load limit	0.62 kN
Limiting speed	3400 r/min
Permissible angular misalignment	2.5 °
Calculation factor	0.04
Limiting value	0.19
Calculation factor	3.6
Calculation factor	3.3
Calculation factor	5.1
Performance	
Basic dynamic load rating	31.2 kN
Basic static load rating	12.2 kN
Reference speed	9000 r/min
Limiting speed	3400 r/min
Properties	
Retaining feature, inner ring	Locating slot
Locating feature, bearing outer ring	Without
Number of rows	2
Bore type	Cylindrical
Cage	Non-metallic
Radial internal clearance	CN
Tolerance class	Normal
Material, bearing	Bearing steel
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	5.2 kg CO ₂ e

Logistics	
Product net weight	1.45 kg
eClass code	23-05-08-06
UNSPSC code	31171532

SKF drawings

