



SKF 6320-2Z/C3

Deep groove ball bearing with seals or shields

Single row deep groove ball bearings with seals or shields are particularly versatile, have low friction and are optimized for low noise and low vibration, which enables high rotational speeds. They accommodate radial and axial loads in both directions, are easy to mount, and require less maintenance than many other bearing types. The integral sealing can significantly prolong bearing service life because it keeps lubricant in the bearings and contaminants out.

Technical specifications

| Dimensions | |
|------------------|--------|
| Bore diameter | 100 mm |
| Outside diameter | 215 mm |
| Width | 47 mm |

| Performance | |
|---------------------------|------------|
| Basic dynamic load rating | 174 kN |
| Basic static load rating | 140 kN |
| Reference speed | 6700 r/min |
| Limiting speed | 3400 r/min |

| Properties | |
|---|-------------------------|
| Filling slots | Without |
| Number of rows | 1 |
| Locating feature, bearing outer ring | Without |
| Bore type | Cylindrical |
| Cage | Sheet metal |
| Matched arrangement | No |
| Radial internal clearance | C3 |
| Material, bearing | Bearing steel |
| Coating | Without |
| Sealing | Shield on both sides |
| Sealing type | Non-contact |
| Lubricant | Grease |
| Relubrication feature | Without |
| Indicative carbon footprint for new product | 25.8 kg CO ₂ |

| Logistics | |
|--------------------|-------------|
| Product net weight | 7.17 kg |
| eClass code | 23-05-08-01 |
| UNSPSC code | 31171504 |