

SKF TMMP 15

Инструмент SKF

Инструменты SKF для монтажа и демонтажа подшипников — ударные ключи, нагреватели, съёмники, гидравлические гайки. Обеспечивают безопасную и точную установку.

Характеристики

Размеры	
Width of grip external	Array mm
Effective arm length	340 mm
Alternative arm lengths	With accessory alternative arms: 260 mm or 435 mm or 685 mm
Claw height	30 mm
Claw length	37 mm
Total Arm length	534 mm
Claw width	12 mm
Spindle head, hexagon size	28
Total spindle length	661 mm

Свойства	
Рекомендуемые применения	For the dismounting of bearings, gears, pulleys and other industrial ring shaped components in industrial, construction and agricultural applications with an interference fit on the shaft
Suitable for workpiece dismounting from a Cylindrical seating (straight shaft)	Да
Suitable for bearing dismounting from a Tapered seating (conical shaft)	Да
Suitable for bearing dismounting from a Sleeve (adapter or withdrawal sleeve)	Да
Suitable for workpiece dismounting from a Blind arrangement (housing with shaft)	Нет
Suitable for workpiece dismounting from a Housing	Нет
Suitable for bearing type(s)	All
Dismounting force generation	Spindle
Special features	Pantograph mechanism for parallel opening of arms with selflocking function, heavy duty version. Alternative arm lengths available.
Number of arms	3
Pulling force (max)	150 kN
Spindle torque (max)	700 N·m
Spindle nose piece	Yes, ø32 mm
Цвет	Black
Материал	Alloy engineering steels, hardened and tempered
Покрытие	Chemical blackened
Content	1x Puller TMMP 15; 1x Printed instructions for use

Логистика	
Масса нетто	21.5 kg
Код eClass	23-05-19-01
Код UNSPSC	27111712