



SKF 61909

Deep groove ball bearing

Single row deep groove ball bearings are particularly versatile, have low friction and are optimized for low noise and low vibration, which enables high rotational speeds. They accommodate radial and axial loads in both directions, are easy to mount, and require less maintenance than many other bearing types.

Technical specifications

Dimensions	
Bore diameter	45 mm
Deviation limits of mid-range bore diameter	-0.01..0 mm
Outside diameter	68 mm
Deviation limits of mid-range outside diameter	-0.011..0 mm
Width	12 mm
Deviation limits of ring width	-0.12..0 mm
Shoulder diameter	52.4 mm
Shoulder diameter	61.2 mm
Chamfer dimension	0.6 mm
ISO tolerance class for dimensions	P6

Abutment dimensions	
Diameter of shaft abutment	48.2 mm
Diameter of housing abutment	64.8 mm
Radius of shaft or housing fillet	0.6 mm

Calculation data	
Basic dynamic load rating	14 kN
Basic static load rating	9.8 kN
Fatigue load limit	0.465 kN
Reference speed	20000 r/min
Limiting speed	13000 r/min
Minimum load factor	0.02
Calculation factor	14.4

Tolerances of run-out	
Range of section height at inner ring of assembled bearing	10 µm
Range of section height at outer ring of assembled bearing	13 µm
ISO tolerance class for geometrical tolerances	P6

Performance	
Basic dynamic load rating	14 kN
Basic static load rating	9.8 kN
Reference speed	20000 r/min
Limiting speed	13000 r/min

Properties	
Filling slots	Without
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Matched arrangement	No
Radial internal clearance	CN
Material, bearing	Bearing steel
Coating	Without
Sealing	Without
Lubricant	None

Relubrication feature	Without
Indicative carbon footprint for new product	0.47 kg CO ₂ e

Logistics	
Product net weight	0.13 kg
eClass code	23-05-08-01
UNSPSC code	31171504

SKF drawings