



SKF 7202 BEP

Single row angular contact ball bearing

These single row angular contact ball bearings can accommodate radial and axial loads acting simultaneously, where the axial load acts in one direction only. They can operate at high speeds and, depending on the variant, even very high speeds. They are more suitable than deep groove ball bearings for supporting large axial forces acting in one direction.

Technical specifications

Dimensions	
Bore diameter	15 mm
Deviation limits of mid-range bore diameter	-0.008..0 mm
Outside diameter	35 mm
Deviation limits of mid-range outside diameter	-0.011..0 mm
Width	11 mm
Deviation limits of ring width	-0.12..0 mm
Shoulder diameter of inner ring (large side face)	23 mm
Shoulder diameter of inner ring (small side face)	18.93 mm
Shoulder diameter of outer ring (large side face)	27.25 mm
Distance side face to pressure point	16 mm
Chamfer dimension	0.6 mm
Chamfer dimension	0.3 mm
ISO tolerance class for dimensions	Normal
Contact angle	40 °

Abutment dimensions	
Diameter of shaft abutment	19.2 mm
Abutment diameter housing	30.8 mm
Diameter of housing abutment	32.6 mm
Radius of fillet	0.6 mm
Radius of fillet	0.3 mm

Calculation data	
Basic dynamic load rating	8.32 kN
Basic static load rating	4.4 kN
Fatigue load limit	0.183 kN
Reference speed	26000 r/min
Limiting speed	24000 r/min
Minimum axial load factor	0.0004
Minimum radial load factor	0.1
Limiting value	1.1
Calculation factor (single, tandem)	0.35
Calculation factor (single, tandem)	0.26
Calculation factor (single, tandem)	0.57
Calculation factor (back-to-back, face-to-face)	0.57
Calculation factor (back-to-back, face-to-face)	0.52
Calculation factor (back-to-back, face-to-face)	0.55
Calculation factor (back-to-back, face-to-face)	0.93

Tolerances of run-out	
Range of section height at inner ring of assembled bearing	10 µm
Range of section height at outer ring of assembled bearing	20 µm
ISO tolerance class for geometrical tolerances	Normal

Performance	
Basic dynamic load rating	8.32 kN
Basic static load rating	4.4 kN

Reference speed	26000 r/min
Limiting speed	24000 r/min

Properties	
Contact type	Normal contact (two-point contact)
Number of rows	1
Locating feature, bearing outer ring	Without
Ring type	One-piece inner and outer rings
Cage	Non-metallic
Matched arrangement	No
Universal matching bearing	No
Axial internal clearance	Not applicable
Tolerance class	Normal
Material, bearing	Bearing steel
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	0.16 kg CO ₂ e

Logistics	
Product net weight	0.0436 kg
eClass code	23-05-08-03
UNSPSC code	31171531

SKF drawings

