



SKF FY 65 TF

Square flanged ball bearing unit with set screw locking, cast iron housing, ISO

These square flanged ball bearing units are compliant with ISO standards. They consist of an insert bearing, with an extended inner ring and set screw locking, and are suitable for applications where the direction of rotation is constant or alternating. The bearing is mounted in a cast iron housing, which can be bolted to a machine wall or frame. Ball bearing units can accommodate moderate initial misalignment, but normally do not permit axial displacement.

Technical specifications

General	
Compliance with standard	ISO
Purpose specific	For agricultural applications
Material, housing	Cast iron
Sealing, bearing	Seal and flinger on both sides
Sealing type, bearing	Contact, standard
Sealing, unit	Optional end cover
Coating	Without

Dimensions	
Bore diameter	65 mm
Outer diameter of inner ring	82.5 mm
Width of housing	52.5 mm
Flange width	17 mm
Depth of centring recess	3.2 mm
Standout of end cover	39 mm
Width of inner ring	68.3 mm
Overall bearing width	68.3 mm
Distance from locking device side face to thread centre	10 mm
Top external diameter	142 mm
Base external diameter	154 mm
Diameter of housing centering recess	161.9 mm
Centre distance between bolt holes	149.5 mm
Overall length	187 mm
Diameter of attachment bolt hole	18 mm
Distance from locking device side face to raceway centre	42.9 mm
Overall width	76.9 mm
Housing thread for grease fitting	1/4-28 UNF
Axial position of the housing thread	34.5 mm
Diameter of head sphere of grease fitting	6.5 mm
Hexagonal key size for the grease fitting	7 mm
Thread of grease fitting	1/4-28 SAE-LT
Distance of dowel pins	169 mm
Axial offset of dowel pins	51 mm
Recommended diameter for dowel pins	4 mm
Attachment bolt diameter	16 mm
Shaft diameter	65 mm
Housing overall width	52.5 mm
Width, total	76.9 mm
Bearing width, total	68.3 mm

Calculation data	
Basic dynamic load rating	57.2 kN
Basic static load rating	40 kN
Fatigue load limit	1.7 kN
Limiting speed	3000 r/min
	Limiting speed with shaft tolerance h6

Mounting information	
Set screw	M10x1
Hexagonal key size for set screw	5 mm
Recommended tightening torque for set screw	16.5 N·m
Recommended diameter for attachment bolts, mm	16 mm
Recommended diameter for attachment bolts, inch	0.625 in

Performance	
Basic dynamic load rating	57.2 kN
Basic static load rating	40 kN
Limiting speed	3000 r/min
Note	Limiting speed with shaft tolerance h6

Properties	
Housing type	Flanged
Flanged housing type	Square
Number of bolt holes for fasteners	4
Fastening bolt hole type	Plain
Retaining feature, inner ring	Set screws
Bore type	Cylindrical
Rubber seating ring	Without
Material, housing	Cast iron
Material, bearing	Bearing steel
Coating	Without
Sealing, bearing	Seal and flinger on both sides
Sealing type	Contact, standard
Sealing, unit	Optional end cover
Lubricant	Grease
Relubrication hole	With
Grease fitting	With

Logistics	
Product net weight	4.78 kg
eClass code	23-05-08-02
UNSPSC code	31171536

SKF drawings

