

SKF TMMR 250F

Инструмент SKF

Инструменты SKF для монтажа и демонтажа подшипников — ударные ключи, нагреватели, съёмники, гидравлические гайки. Обеспечивают безопасную и точную установку.

Характеристики

Логистика	
Масса нетто	4.21 kg
Код eClass	23-05-19-01
Код UNSPSC	27111712

Свойства	
Рекомендуемые применения	For the dismounting of bearings, gears, pulleys and other industrial ring shaped components in industrial, construction and agricultural applications with an interference fit on the shaft
Suitable for workpiece dismounting from a Cylindrical seating (straight shaft)	Да
Suitable for bearing dismounting from a Tapered seating (conical shaft)	Да
Suitable for bearing dismounting from a Sleeve (adapter or withdrawal sleeve)	Да
Suitable for workpiece dismounting from a Blind arrangement (housing with shaft)	Нет
Suitable for workpiece dismounting from a Housing	Yes, with spindle support (not included)
Suitable for bearing type(s)	All
Dismounting force generation	Spindle
Special features	Reversible arms;Selflocking arms
Number of arms	2
Width of grip external	Array mm
Width of grip internal	Array mm
Effective arm length	183 mm
Total Arm length	245 mm
Claw height	10 mm
Claw length	22 mm
Claw width	28 mm
Spindle torque (max)	160 N·m
Spindle head, hexagon size	24
Puller or Adapter hexagon size	32 mm
Spindle nose piece	No, optional
Материал	Alloy engineering steels, hardened and tempered
Покрытие	Zinc coated
Content	1x Puller TMMR 250F;1x Tube of spindle grease LGV2/0.035;1x Printed instructions for use

Размеры	
Total spindle length	317 mm