



SKF NA 4909.2RS

Single row needle roller bearing with machined rings, with flanges and integral seal

Single row needle roller bearings incorporate cylindrical rollers that are small in diameter relative to their length. Owing to their large number of rollers, the bearings have a high load carrying capacity. The outer ring includes two integral flanges to guide the bearing axially and an annular groove with one or more lubrication holes to facilitate relubrication. The inner ring contains an additional lubrication hole.

Technical specifications

Dimensions	
Bore diameter	45 mm
Outside diameter	68 mm
Width	23 mm
Width outer ring	22 mm
Raceway diameter inner ring	52 mm
Chamfer dimension outer ring	0.6 mm
Permissible axial displacement from the normal position of one bearing ring relative to the other	0.5 mm

Abutment dimensions	
Smallest permissible abutment diameter shaft, bearings with flanges	49 mm
Diameter of housing abutment	64 mm
Fillet radius	0.6 mm

Calculation data	
SKF performance class	SKF Explorer
Basic dynamic load rating	45 kN
Basic static load rating	64 kN
Fatigue load limit	8 kN
Reference speed	7500 r/min
Limiting speed	3800 r/min

Performance	
Basic dynamic load rating	45 kN
Basic static load rating	64 kN
Reference speed	7500 r/min
Limiting speed	3800 r/min
SKF performance class	SKF Explorer

Properties	
Bearing part	Complete bearing
Number of rows	1
Outer ring type	Machined (solid)
Aligning feature	Without
Cage	Sheet metal
Number of flanges, outer ring	2
Radial internal clearance	CN
Tolerance class	Normal
Material, bearing	Bearing steel
Coating	Without
Sealing	Seal on both sides
Sealing type	Contact
Lubricant	Grease
Relubrication feature	With
Indicative carbon footprint for new product	1 kg CO ₂ e

Logistics	
Product net weight	0.28 kg
eClass code	23-05-09-03
UNSPSC code	31171512

SKF drawings

