

SKF TMFN 64-80

Impact Spanner

The TMFN impact spanners are designed for safely tightening and loosening larger locknuts, especially after driving up a large bearing onto a tapered seating. Made of spheroidal graphite cast iron, they have a special impact surface allowing for optimum transmission of impact energy to the nut.

Technical specifications

Dimensions	
Locknut size	Array
Outer diameter lock nut (range) (d ₃)	Array mm
Handle length (L _h)	388 mm
Nose width (N _k)	35 mm
Nose height (N _h)	11 mm
Nose Length (f)	23 mm
Thickness (n)	35 mm
Length (L)	475 mm
Working length (l)	600 mm

Properties	
Recommended applications	To safely tighten or loosen lock nuts after driving up large bearings on tapered seatings when working with rotating components in variety of applications with medium to large bearings and lock nuts.
Series	Impact spanner, TMFN
Type	Model E
Allows bearing mounting	No
Fits on lock nuts inside SKF split pillow block housings (SNL)	No
Suitable SKF Locknut	HM 3068, HM 3070, HM 3072, HM 3074, HM 3076, HM 3078, HM 3080, HM 3082, HM 3084, HM 3164, HM 3166, HM 3168, HM 3170, HM 3172, HM 3174, HM 3176, HME 3068, HME 3070, HME 3072, HME 3074, HME 3076, HME 3078, HME 3080, HME 3082, HME 3084, HME 3164, HME 3166, HME 3168, HME 3170, HME 3172, HME 3174, HME 3176, N 068, N 070, N 072, N 074, N 076, N 076, N 078, N 080, N 080, N 082, N 084
Handle fixation	Pivotable
Material	Head: spheroidal cast iron;Handle: carbon steel
Material handle	Steel handle with rubber grip
Coating	Black phosphated head with galvanized handle
Colour	Black metallic, silver

Logistics	
Product net weight	4.55 kg
eClass code	23-05-19-01
UNSPSC code	27111712