



SKF 32324

Single row tapered roller bearing

Single row tapered roller bearings are designed to accommodate combined radial and axial loads and provide low friction during operation. The inner ring, with rollers and cage, can be mounted separately from the outer ring. These separable and interchangeable components facilitate mounting, dismounting and maintenance. By mounting one single row tapered roller bearing against another and applying a preload, a rigid bearing application can be achieved.

Technical specifications

General	
Dimension series	2GD
Dimensions	
Bore diameter	120 mm
Outside diameter	260 mm
Bearing width, total	90.5 mm
Shoulder diameter of inner ring	181.5 mm
Width of inner ring	86 mm
Width of outer ring	69 mm
Chamfer dimension of inner ring	4 mm
Chamfer dimension of outer ring	3 mm
Distance side face to pressure point	59.667 mm
Width, total	90.5 mm
Width, inner ring	86 mm
Width, outer ring	69 mm
Contact angle	13 °
Abutment dimensions	
Diameter of shaft abutment	148 mm
Diameter of shaft abutment	136.5 mm
Diameter of housing abutment	213 mm
Diameter of housing abutment	246.5 mm
Diameter of housing abutment	239 mm
Minimum width of space required in housing on large side face	10 mm
Minimum width of space required in housing on small side face	21.5 mm
Radius of shaft fillet	4 mm
Radius of housing fillet	3 mm
Calculation data	
Basic dynamic load rating	855 kN
Basic static load rating	1120 kN
Fatigue load limit	110 kN
Reference speed	1800 r/min
Limiting speed	2600 r/min
Limiting value	0.35
Calculation factor	1.7
Calculation factor	0.9
Performance	
Basic dynamic load rating	855 kN
Basic static load rating	1120 kN
Reference speed	1800 r/min
Limiting speed	2600 r/min
Properties	
Bearing part	Complete bearing
Number of rows	1

Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Sheet metal
Arrangement of contact angle (double-row bearing)	Not applicable
Matched arrangement	No
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Unit system	Metric
Indicative carbon footprint for new product	76.9 kg CO ₂ e

Logistics	
Product net weight	21.4 kg
eClass code	23-05-09-10
UNSPSC code	31171516

SKF drawings