



SKF NKIS 60

Single row needle roller bearing with machined rings, with flanges

Single row needle roller bearings incorporate cylindrical rollers that are small in diameter relative to their length. Owing to their large number of rollers, the bearings have a high load carrying capacity. The outer ring includes two integral flanges to guide the bearing axially and an annular groove with one or more lubrication holes to facilitate relubrication.

Technical specifications

Dimensions	
Bore diameter	60 mm
Outside diameter	90 mm
Width	28 mm
Raceway diameter inner ring	70 mm
Chamfer dimension outer ring	1.1 mm
Permissible axial displacement from the normal position of one bearing ring relative to the other	2 mm

Abutment dimensions	
Smallest permissible abutment diameter shaft, bearings with flanges	66.5 mm
Diameter of housing abutment	83.5 mm
Fillet radius	1 mm

Calculation data	
SKF performance class	SKF Explorer
Basic dynamic load rating	78 kN
Basic static load rating	120 kN
Fatigue load limit	15.3 kN
Reference speed	5600 r/min
Limiting speed	6300 r/min

Performance	
Basic dynamic load rating	78 kN
Basic static load rating	120 kN
Reference speed	5600 r/min
Limiting speed	6300 r/min
SKF performance class	SKF Explorer

Properties	
Bearing part	Complete bearing
Number of rows	1
Outer ring type	Machined (solid)
Aligning feature	Without
Cage	Sheet metal
Number of flanges, outer ring	2
Radial internal clearance	CN
Tolerance class	Normal
Material, bearing	Bearing steel
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	With
Indicative carbon footprint for new product	2.2 kg CO ₂

Logistics	
Product net weight	0.596 kg

eClass code	23-05-09-03
UNSPSC code	31171512

SKF drawings

